



### **45cbm 45000l Carbon Steel Oil Tanker Semi Trailer with 5 Compartments**

JUPITER® is a leading China Fuel Tanker Semi Trailer manufacturer, supplier and exporter. Adhering to the pursuit of perfect quality of products, so that our 45cbm 45000l Carbon Steel Oil Tanker Semi Trailer with 5 Compartments have been satisfied by many customers. Extreme design, quality raw materials, high performance and competitive price are what every customer wants, and that's also what we can offer you. Of course, also essential is our perfect after-sales service. If you are interested in our tanker semi trailer services, you can consult us now, we will reply to you in time!

### **Product Description**

#### **Features of JUPITER® 45cbm 45000l Carbon Steel Oil Tanker Semi Trailer with 5 Compartments**

1. Tri- axle oil tanker trailer is designed in accordance with ADR standard
2. Popular in the Philippines and the Middle East (Saudi Arabia, Oman, Kuwait, etc.) and West Africa (Gabon, Ghana, Mali, Burkina Faso, etc.) markets.
3. It can be made into 30,000,40,000 and 45,000 Liters Fuel tank trailer with 3 to 9 compartments.
4. Tanker is a sealed loading container, advanced equipment is be used to ensure the welding quality.
5. This tanker trailers will be shipped by bulk ship or Flat Rack. We keep long- term cooperation with ship agency that can give you a lowest shipping cost.
6. Our raw material and OEM parts are purchased centralized by Professional team, every node will be inspected strictly. Also some easily broken parts will be delivered with the trailers.

## **TECHNICAL HIGHLIGHTS**

- FUWA,BPW or Certificated China Axles
- Bottom Loading System
- Hydraulic or Pneumatic Handrail
- High Quality Steel usage
- Air or Mechanical or Hydraulic Suspension
- Capacity and Compartments As Per The Buyer Request

### **40KL PETROLEUM GASOLINE DIESEL FUEL TANKER SEMI TRAILER**

Model:	JPT9405GY
--------	-----------

Dimensions:	
Length:	11,800mm
Width:	2,500mm
Height:	3,860mm
Kingpin Location:	950mm from the front face of the front bolster
Axle Spacer:	6,600mm + 1,310mm + 1,310mm
Landing Gear Location:	2,500mm from the kingpin center to the landing gear
Weight:	
Payload:	40,000Kg
Tare Weight:	Approx. 11,500Kg.
G.V.W.R:	Approx. 51,500Kg
Tank:	
Volume:	40,000L + 5% Vapor
Compartment:	9 (6-4-6-4-2-6-2-6-4)
Tank Body & Dish End:	Carbon Steel Q345B, Thickness: 5mm,&Thickness: 6mm
Compartment Plate:	Carbon Steel Q345B, Thickness: 5mm
Design Standard:	Straight Cylindrical Tank.
Bottom Safety Valve:	JIALONG, 9 Pcs. (One 4" pneumatical emergency valve per compartment - EURO; One 4"x3" Gravity Adaptor with sight glass per compartment; One 4" API Valve and dust cover per compartment)
API Cap:	JIALONG 9 Pcs.
Combination Switch:	JIALONG, Air Operated, 1 Sets
Emergency Switch:	Factory Standard, with cover box, 2 Pcs.
Discharge	4", Discharge Valves are angled at approximately 5 Degrees downward.

Valve:	
Discharge Pipe:	
API Reduction Connector:	3"
Discharge Hose:	3"
Manhole:	JIALONG, 20inches, Aluminum, 9 pcs., with Anti- Theft design. With braath Valve
Capacity Indicators:	Factory Standard, 9 Pcs.
Oil Water Separator:	Factory Standard, 1 Pc.
Working Pressure:	0.2 Mpa
Test Pressure:	0.3 Mpa
Welding Standard:	All welding are to be done by qualified welder per applicable national standard. X-Ray checking.
Painting:	Shot blast at SA 2.5 prior to application of primer, polyurethane top coat. Total DFT not less than 100um.
Running Gear:	
Kingpin:	JOST, KZ1012-50, 2 inches Bolted Type
Suspension:	FUWA Brand Mechanical Suspension with 10 pcs Leaf Spring: 13mm Thinkness x 90mm Width.
Axle:	FUWA 150x150 Square Beam Axle, 3Pcs.*13 Ton Capacity
Brake System:	Dual line Pneumatic Brake, with Hose & Connector.
ABS System:	4S/2M
Brake Chamber:	T30/30 Spring Brake System on 2 Axles
Air Tank:	50L, 2Pcs.
Emergency Relay Valve:	WABCO BRAND

Rim:	9.0-22.5, 10 Holes ISO, 14 Pcs. (Included 2 Spare Tires)
Tire:	AEOLUS 12R22.5, 14 Pcs. (Included 2 Spare Tires)
Landing Gear:	JOST E100 Two Speed Telescopic manual landing gear
Electrical System:	
Voltage:	24V
Receptacle:	7 Way Socket
Front Marker Lamp:	LED Lights, included Front Marker Lamp, Side Marker Lamp, Turn Signal Lamp, Rear Lamp. Electric cable protected by PVC conduit on main frame.
Reflector:	Triangle Reflector, Red Color
Wiring:	FLAMMABLE NO SMOKING WITHIN 50 FEET
Accessories:	
Common Line Discharge Valve:	Carbon Steel pipe with 4" Discharge Valve, included a 3" or 2.5" Adaptor
Fire Extinguisher:	10 Kgs. Type, 2 Sets.
Mud Guard:	Rubber mud guard with brush
Walkway:	YELLOW Colour, Anti-Slip Painting.
Handrail:	800mm Height, Pneumatic Controlling
Wheel Stopper:	2 Pcs.
Spare Wheel Carriers:	Q345, 2 Pcs.
Fender:	Black Plastic Type, with Brush, 6 Pcs.
Rail:	Pneumatic Control Hand Rail, Both Side, Aluminum Type
Tool Box:	800mm Length, 2 Pcs.
Pipe:	One Piece of 4" Diameter*6m length pipe each tank, for customer use.
Ladder:	Carbon Steel Type, Front Design

Bumper:	1 Set Rear Bumper, 1 Set Rear Secondary Bumper, 1 Set Side under Run,
---------	---

